

MODEL	VOLTAGE		NO LOAD		AT MAXIMUM EFFICIENCY					STALL		
	OPERATING RANGE	NOMINAL	SPEED	CURRENT	SPEED	CURRENT	TORQUE		OUTPUT	TORQUE		CURRENT
			rpm	A	rpm	A	g.cm	mN.m	W	g.cm	mN.m	A
YG300R-11440	0.7-5.0	2V DC	2200	0.018	1660	0.055	2.9	0.28	0.049	12	1.18	0.17
YG300R-11400	1.2-6.0	3V DC	3700	0.018	2970	0.073	3.8	0.37	0.12	20	1.96	0.30
YG300R-09550	1-6	3V DC	2700	0.012	2100	0.042	2.8	0.27	0.06	13	1.28	0.15
YG300R-14270	0.5-4.0	1.9V DC	3500	0.032	2740	0.120	3.9	0.38	0.11	18	1.77	0.42
YG300R-1D390	2.8-7.0	3.9V DC	4400	0.021	3520	0.084	4.8	0.47	0.17	24	2.35	0.34
YG300R-11420	0.7-5.0	3V DC	2900	0.017	2320	0.068	4.3	0.42	0.10	22	2.16	0.27
YG300R-12350	1.5-6.0	3V DC	3500	0.022	2830	0.093	4.9	0.48	0.14	26	2.55	0.39