

Tamaño EI 30/10.5T
 Size EI 30/10.5T


Potencia 1.2VA
 Power output 1.2VA

Temperatura trabajo / Clase térmica T70/B
 Temperature / Thermal class T70/B


Modelo Model	Secundario Secondary	ta clase ta class	Protección Protection	Homologaciones Approvals	
				115V	230V
1123014	1122093 6V-0.2A	ta 70/B	Cortocircuitables Short-circuitable	2-4-5	2-3-4-5
1123015	1122094 7.5V-0.16A	ta 70/B		2-4-5	2-3-4-5
1123016	1122095 9V-0.13A	ta 70/B		2-4-5	2-3-4-5
1123017	1122096 12V-0.1A	ta 70/B		2-4-5	2-3-4-5
1123018	1122097 15V-0.08A	ta 70/B		2-4-5	2-3-4-5
1123019	1122098 18V-0.066A	ta 70/B		2-4-5	2-3-4-5
1123020	1122099 24V-0.05A	ta 70/B		2-4-5	2-3-4-5

Modelo Model	Secundario Secondary	ta clase ta class	Protección Protection	Homologaciones Approvals	
				115V	230V
1123021	1122100 2x6V-2x0.1A	ta 70/B	Cortocircuitables Short-circuitable	2-4-5	2-3-4-5
1123022	1122101 2x7.5V-2x0.08A	ta 70/B		2-4-5	2-3-4-5
1123023	1122102 2x9V-2x0.066A	ta 70/B		2-4-5	2-3-4-5
1123024	1122103 2x12V-2x0.05A	ta 70/B		2-4-5	2-3-4-5
1123025	1122104 2x15V-2x0.04A	ta 70/B		2-4-5	2-3-4-5
1123026*	1122105* 2x18V-2x0.033A	ta 70/B		2-4	2-3-4
1123027*	1122106* 2x24V-2x0.025A	ta 70/B		2-4	2-3-4

Dimensiones mm. (inches)
 Dimensions mm. (inches)



EI 30/10.5T




Pri. = 1-5 (115V ó 230V)
 1 Sec. = 7-9
 2 Sec. = 6-7 / 9-10


Esquema eléctrico
 Electric arrangement

Conexión Secundario / Secondary Connections

Esquema
 Circuit arrangement



Conexión serie
 Serial connection



Conexión paralelo
 Parallel connection

